



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : C06C 7/00, C06B 45/34</p>	<p>A1</p>	<p>(11) International Publication Number: WO 99/44968 (43) International Publication Date: 10 September 1999 (10.09.99)</p>
<p>(21) International Application Number: PCT/CA98/00182 (22) International Filing Date: 6 March 1998 (06.03.98) (71) Applicant (<i>for all designated States except US</i>): SNC INDUSTRIAL TECHNOLOGIES INC. / LES TECHNOLOGIES INDUSTRIELLES SNC INC. [CA/CA]; 5 Montee des Arsenaux, Le Gardeur, Quebec J5Z 2P4 (CA). (72) Inventors; and (75) Inventors/Applicants (<i>for US only</i>): GUINDON, Louise [CA/CA]; 1679 De Lunebourg, Vimont Laval, Quebec H7M 4J7 (CA). LEPAGE, Daniel [CA/CA]; 673 Beauchamp, Le Gardeur, Quebec J5Z 3A6 (CA). DROLET, Jean-Pierre [CA/CA]; 11770 Place de Guise, Quebec, Quebec G2A 3K7 (CA). (74) Agent: FRENCH, David, J.; P.O. Box 2486, Station D, Ottawa, Ontario K1P 5W6 (CA).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report.</i></p>
<p>(54) Title: NON-TOXIC PRIMERS FOR SMALL CALIBER AMMUNITION</p> <p>(57) Abstract</p> <p>A non-toxic primer composition for use in ammunition is provided with a hygroscopic oxidizer which is protected from absorption of water vapour by a water-barrier coating. A preferred oxidizer is potassium nitrate and a preferred coating is nitrocellulose.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

NON-TOXIC PRIMERS FOR SMALL CALIBER AMMUNITION

FIELD OF THE INVENTION

This invention relates to non-toxic primers in the field of small caliber ammunition. In particular, it relates to
5 non-toxic primers which can be used in all types of small arms ammunition, including reduced energy cartridges.

BACKGROUND OF THE INVENTION

Many publications and articles collected, for example, by the SAAMI (Sporting Arms and Ammunition Manufacturers' Institute) Environmental Committee clearly indicate the
10 necessity for environment-friendly ("green") ammunition. The military is also moving in the same direction. For small caliber ammunition, the principal culprit in producing gaseous combustion products during firing that
15 may be inhaled by the shooter (in the form of dust or oxides of toxic elements) is the primer. Small caliber ammunition is fired in large quantities both in indoor ranges for training or practice and outdoors for both of these reasons as well as for hunting, sporting events (trap
20 shooting, biathlon, etc.) and military simulations.

Specifically, as detailed in the EPA (Environmental Protection Agency) list of toxic materials and the FBI (Federal Bureau of Investigation) list of toxic metals,

there is a need to eliminate mercury, lead, barium, antimony, beryllium, cadmium, arsenic, chromium, selenium, tin and thallium from primer compositions. This means that long-standing chemically-stable, reliable non-corrosive primer compositions containing lead, barium, antimony or other metallic compounds are no longer acceptable from an environmental point of view. Unfortunately, primers containing such ingredients are still in wide use because suitable alternatives have not yet been found that eliminate all toxic materials as well as meeting ballistic reliability requirements and price realism.

There is much prior art. Going back to 1982, the following US patents are relevant: 4,363,679; 4,522,665; 4,566,921; 4,581,082; 4,608,102; 4,674,409; 4,675,059; 4,689,185; 4,963,201; 5,167,736; 5,353,707; 5,388,519, 5,417,160, 5,466,315 (Erickson) and 5,547,528 (Erickson). In addition there are European patent N° 699 646 and French Patent N° 9602359.

Many of these patents cite diazodinitrophenol (DDNP or dinol) as the primary explosive in combination with one or more oxidizers along with a variety of other ingredients necessary for the proper functioning of a primer. The oxidizers for primers cited in the prior art listed above include zinc peroxide, manganese dioxide, strontium peroxide, strontium nitrate, calcium carbonate, cupric

oxide, ferric oxide, cesium nitrate, sodium oxalate, zirconium oxide and stannic oxide.

One oxidizer that does not appear prominently on this list is potassium nitrate (KNO_3). This lack of interest is undoubtedly because KNO_3 is hygroscopic (water solubility is 31.6 g/100 ml @ 20°C). Any primer ingredient that has a tendency to attract or absorb water is not acceptable because of the negative effect on primer ignition, which manifests itself through misfires. The two Erickson patents listed above address the question of hygroscopicity, but neither uses KNO_3 as an ingredient.

US Patent N° 3,348,985 describes a gas-generating pyrotechnic composition for such uses as propellant charges for cartridges, missile propulsion, and to assist the take-off of military and commercial aircraft. This composition contains a small amount of KNO_3 (< 9%) which is a component of the principal oxidizer in its as-purchased state and, as such, must be tolerated. US Patent N° 5,417,160 utilizes KNO_3 as an oxidizer in primers, but always in combination with calcium silicide.

One way to make KNO_3 immune to water (i.e., to "waterproof" it) is to coat it prior to incorporation into the mix with a thin layer of nitrocellulose (NC), amounting to about 1% by weight of the formulation, as described in this invention. There is prior art unrelated to primers

which describes the use of NC in formulations also containing KNO_3 , but not for the purposes of coating the KNO_3 . For example, US Patent N° 5,125,684 describes a gas-generating propellant for use in a vehicle occupant
5 restraint system which contains KNO_3 (>50% by weight) as an oxidizer and NC (20%) as a binder and principal combustion ingredient. US Patent N° 5,495,807 also deals with a gas-generating module for an airbag utilized in motor vehicles in which the gas-generating composition is arranged within
10 a container in "the shape of a foil-like layer or coating, or alternatively consists of a granulate" with a first binder of NC (2% by weight) to give consistency to the mix during kneading prior to granulation.

An objective of this invention is to find a way to
15 utilize a hygroscopic oxidizer KNO_3 as the primary and predominant oxidizer (> 50% by weight of the oxidizer content) in a primer free of toxic materials in such a way that the ballistic performance of the primer will meet all performance specifications routinely required for small
20 caliber ammunition. This will be done by demonstrating that KNO_3 can be utilized as a reliable primary oxidizer if suitably coated beforehand to eliminate its hygroscopic nature.

The invention in its general form will first be
25 described, and then its implementation in terms of specific

embodiments will be detailed hereafter. These embodiments are intended to demonstrate the principle of the invention, and the manner of its implementation. The invention in its broadest and more specific forms will then be further
5 described, and defined, in each of the individual claims which conclude this Specification.

SUMMARY OF THE INVENTION

The invention according to one aspect relies upon the presence in a primer composition of a hygroscopic
10 oxidizer which is combined with waterproofing vapour barrier material to protect the oxidizer from undue absorption of atmospheric water vapour. A preferred oxidizer is potassium nitrate (KNO_3), which is coated with nitrocellulose, as a preferred coating material to protect
15 the KNO_3 from its hygroscopic nature. Sufficient nitrocellulose coating is provided to ensure that the performance of KNO_3 as an oxidizer is not degraded by the presence of water that would otherwise be absorbed by the KNO_3 from the environment. Other oxidizers susceptible to
20 moisture absorption, e.g. strontium nitrate $\text{Sr}(\text{NO}_3)_2$ can be similarly protected.

More preferably, the primer mix is free of toxic metals e.g. lead, barium, antimony. In a non-toxic primer DDNP may be employed as the primary explosive and

optionally, PETN may be present as a secondary explosive. Tetrazene may be added to increase sensitivity to friction. Also optionally $\text{ZnO} \cdot \text{ZnO}_2$ (containing at least 50-60% of ZnO_2) may be present as a secondary oxidizer, with KNO_3 predominating as the principal source of oxygen.

As further preferred constituents of the primer composition, silicon carbide (carborundum) may be present to increase sensitivity to friction (i.e. as a "frictionator") and aluminum powder may be used as the fuel.

More particularly, the preferred composition for the primer composition of the invention is shown in Table 1.

DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention is directed towards a non-toxic primer composition containing DDNP as its primary explosive and KNO_3 as its primary oxidizer to be used in all types of small arms ammunition, including reduced energy cartridges as represented by US Patent N° 5,359,937, such cartridges containing only a very small propellant charge. Specifications for this primer composition were set as follows:

- Action time < 4 ms at -54°C (as per NATO Specification D-74-305-A00/SF-001).

- Particles generated by primer sufficiently "hot" to ignite very small propellant charges.
 - Sensitivity according to SAAMI specifications:
- 5 $\bar{H} - 2\sigma = 1$ inch and $\bar{H} + 4\sigma = 11$ inches where \bar{H} is the average height at which 50% misfires occur.
- Sensitivity according to NATO specifications:
(mass of ball = 111.70 g)
- $\bar{H} - 2\sigma > = 75$ mm $\bar{H} + 5\sigma < = 450$ mm
- No loss in sensitivity over time.
- 10 Raw materials readily available at reasonable prices.
- Cost of producing primer comparable to market price of competing primers.

A wet mix manufacturing process was adopted for safety
15 reasons. The ingredients were judiciously selected with reference to the EPA and FBI lists previously mentioned as well as particulate and fume toxicity data published by such recognized authorities as OSHA (Office of Safety and Health Administration), ACGIH (American Conference of
20 Government and Industrial Hygienists), NIOSH (National Institute for Occupational and Safety and Health) and COSHR (Canadian Occupational Safety and Health Regulations).

Thermal gravimetric analyses (TGA) and differential thermal analyses (DTA) were conducted to identify
25 endothermic and exothermic reactions between potential

oxidizers and fuels. The preferred mix was determined by using a ternary phase diagram where the weight concentration on each of the three axes represented the primary explosive, the primary oxidizer and the secondary
5 oxidizer. Based on sensitivity requirements, an area within the triangle was identified for further iterations to optimize concentrations of fuel and friction agent, the other two principal ingredients in the composition.

DDNP was selected based on its favourable historic
10 performance in other types of reduced-toxicity primers and because it is readily produced from available raw materials. PETN was added as a secondary explosive to generate more heat after ignition of the DDNP. Tetrazene was also added to increase sensitivity to friction.

15 Eight oxidizers (carbonate and nitrate compounds along with a few metallic oxides) were assessed for sensitivity and other ballistic considerations. After taking cost into account, KNO_3 and the binary ceramic oxide compound $\text{ZnO} \cdot \text{ZnO}_2$ (containing at least 50 to 60% of ZnO_2) were respectively
20 selected as primary and secondary oxidizers. With respect to the prior art, it was necessary to make KNO_3 predominant over the secondary $\text{ZnO} \cdot \text{ZnO}_2$ (i.e., $\text{KNO}_3 > 50\%$ by weight of the the total oxidizer content).

Prior to incorporation into the mix, the KNO_3 crystals
25 had to be protected so as to negate their hygroscopic

tendencies. To do this, a material that was insoluble in water was needed to coat the water-soluble KNO_3 . There were several plastic candidates suitable for the job, but they would not have contributed to the combustion process, being essentially inert. It was thought, however, that NC would meet all three requirements: (1) water insolubility; (2) an active combustion ingredient; and (3) be susceptible to deposition on KNO_3 crystals. Subsequent testing proved this to be so. Primer mixes containing coated KNO_3 always met the drop test specifications whereas mixes containing uncoated KNO_3 yielded erratic drop test results that did not always meet the specification. The coating process is also applicable to other hygroscopic oxidizers, such as strontium nitrate, without known antagonistic reactions.

The secondary oxidizer selected was the binary ceramic oxide compound $\text{ZnO} \cdot \text{ZnO}_2$ containing 50 to 60% of zinc peroxide (ZnO_2). Three fuels (titanium, zirconium and aluminum) were assessed and the best was found to be aluminum powder due to its favourable performance/price ratio. Silicon carbide (carborundum) was added to the composition to further increase sensitivity to friction and to provide hot particles to ease ignition of percussion primers. It was selected from a group of eleven candidates that were assessed. Finally, a binder was added to

facilitate the compaction of the priming mix into primer cups and to prevent powder loss during subsequent handling.

Based on this approach, the preferred ingredients for a priming composition which meets the objectives of this invention are shown in Table 1. Various ratios of the ingredients, as indicated in the column of Table 1 giving weight ranges, can be used depending on the desired characteristics of the final product. An optimum composition, as detailed in the preferred weight column of Table 1, was determined based on sensitivity to impact and friction tests, sensitivity to drop tests, the quantity of gas generated after ignition in a closed bomb, ease of control of charge weight in primer cups, and ballistic performance when fired in reduced energy cartridges as represented by US Patent N° 5,359,937.

As already stated above, the preferred primer composition is shown in Table 1. The DDNP used had a molecular weight of 210 g, a density of 1.63 g/cc, and an ignition temperature of 200°C. Its particle size distribution was approximately 80% > 50 µm and 20% < 50 µm. The PETN used met MIL-P-387 specifications and had a particle size of about 100 µm. The tetrazrene was manufactured according to MIL-T-46938.

KNO₃ powder (Class 2, MIL-P-156) was added to a previously-prepared 3% solution of NC in acetone and the

resulting slurry was mixed in an appropriate blender before being dried at 60°C for 24 h and then ground to a particle size of about 100 μm . This grinding process may expose portions of the KNO_3 to the atmosphere, but a sufficient
5 amount of KNO_3 remains either fully or partially coated to provide the necessary resistance to moisture absorption. "Coating" as used herein reflects this degree of coverage of the oxidizer as described.

The $\text{ZnO} \cdot \text{ZnO}_2$ (at least 50 to 60% ZnO_2) had a particle
10 size < 45 μm , the aluminum powder (< 45 μm) was according to MIL-A-512A and the SiC was of a commercial grade (approx 100 μm). The binder was an acrylic resin.

To prepare the mix, the explosive ingredients were mixed together with the DDNP initially containing 30 to 40%
15 water, the PETN containing 15% water, and the tetrazene 20 to 30% water. Next, the non-explosive ingredients, including KNO_3 previously coated with NC, were mixed dry separately. The dry non-explosive mixture was then added to the wet mixture of explosive ingredients and thoroughly
20 mixed. The water content was maintained at 15%, by adding additional water if necessary. Finally, the binder was added and a final mixing performed. The finished mix was stored at 4°C prior to use.

During loading, the mix was pressed through a standard
25 perforated primer plate to form pellets of the desired size

for loading into primer cups. Since DDNP is much lighter than the lead styphnate usually used as the primary explosive in conventional primers, the nominal weight of the charge was reduced by about 30%. The resultant charge
5 weight was 12.6 g.

After charging the cups, a lacquered paper was tamped onto the wet charge, and the charge was compacted. A layer of sealing lacquer was placed on top of the foil before drying the primers at 50°C. Following drying, the primers
10 were inserted into cartridge cases in preparation for ballistic evaluation. In all respects, the method of preparing the primers followed general well-known procedures in the field. Physical dimensions of primer cups and anvils were closely controlled as were the overall
15 height of assembled primers and the depth of insertion into primer pockets.

Primers containing the non-toxic mix were subjected to the conventional SAAMI drop test using a 1.94 oz (55 g) weight dropped onto a rifle firing pin. Run-down tests
20 were conducted at heights varying from 1 to 11 inches (25 to 280 mm) in order to obtain the average drop height-H at which 50% of the primers fired and 50% failed to fire. Over 50 such tests were conducted.

Sensitivity to friction and impact was determined by
25 dropping a 1.0 kg weight along a 45° inclined plane onto

either a dry or wet sample located at the bottom of the plane on a rough surface. The vertical height of the plane was 210 cm for the wet sample and 10 cm for the dry sample. The acceptance criterion for both was no detonation and no sparks when the weight impacted the samples.

Finally, standard function and casualty tests were conducted using reduced-energy cartridges as represented by US Patent N° 5,359,937 in many pistols and submachineguns modified to fire this type of ammunition, as well as in many revolvers. With both types of weapons, the action time was measured to detect if there were any problems related to slow ignition or to hangfires. The pistols included: the SIG Sauer P226, P227 and P229 (both 9 mm and .40SW); the H&K MP5A2/A3 and MP5SD; the Beretta 92F and 96D; the Browning HP; the Smith & Wesson 5904, 5946 and 4006; the Glock 17; and the Colt M16A2 and M4. The revolvers included: Smith & Wesson Models 10, 13, 14 and 64; Ruger Models SP-100 and SP-101; and Tarus Models 65 and 82. Firings were also conducted in the Mosberg 500 Remington 870 shotguns.

The results from all these tests are given in Table 2. As can be seen, they clearly show that the non-toxic primer described herein is satisfactory for its intended purpose. The invention being thus described, it is obvious that the non-toxic primer formulation can be varied in many ways.

14

For example, by using a different particle size for the friction agent (60 μm instead of 100 μm) there will be a slight modification to the drop test sensitivity, although always staying within acceptable limits. Such variations
5 in the ingredients are not to be regarded as a departure from the spirit and scope of the invention and all such variations are intended to be included herein.

CONCLUSION

The foregoing has constituted a description of
10 specific embodiments showing how the invention may be applied and put into use. These embodiments are only exemplary. The invention in its broadest, and more specific aspects, is further described and defined in the claims which now follow.

15 These claims, and the language used therein, are to be understood in terms of the variants of the invention which have been described. They are not to be restricted to such variants, but are to be read as covering the full scope of the invention as is implicit within the invention and the
20 disclosure that has been provided herein.

	Formulation	Ingredient	% Weight (Range)	% Weight (Preferred)
	Primary explosive	DDNP	20-30	30
5	Secondary explosive	PETN	2 - 4	2
	Ternary explosive	Tetrazene	7 - 12	8
	Primary oxidizer (coated with NC)	KNO_3	25 - 30	26
10	Coating on KNO_3	Nitrocellulose	0.5 - 1.5	1
	Secondary oxidizer	$\text{ZnO} \cdot \text{ZnO}_2$	15 - 20	17
	Friction agent	SiC	5 - 7	7
	Fuel	Aluminum	5 - 10	8
15	Binder	Acrylic resin	1	1

Table 1 - Range and Preferred Levels of Ingredients for
Non-Toxic Primers

5

Test	Results
Friction and Impact Test (Wet)	No detonation; no sparks
Friction and Impact Test (Dry)	No detonation; no sparks
Drop Tests (SAAMI)	$\bar{H} - 2\sigma = 3.96 \text{ inches (100mm)}$ $\bar{H} + 4\sigma = 8.22 \text{ inches (208mm)}$
Action Time at -54°C	1.5 ms
Function and Casualty	All weapons OK

10

Table 2 - Summary of Test Results

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A primer composition comprising a hygroscopic oxidizer which is combined with waterproofing vapour
5 barrier material to protect the oxidizer from undue absorption of water vapour.
2. A primer composition as in claim 1 wherein the barrier material is a nitrocellulose coating.
3. A primer composition as in claim 1 wherein a
10 predominant component of the oxidizer is KNO_3 which is coated with said barrier material.
4. A primer composition as in claim 1 wherein a predominant component of the oxidizer is strontium nitrate, $\text{Sr}(\text{NO}_3)_2$.
- 15 5. A primer composition as in claim 1 that is free of toxic metals selected from the group consisting of: lead, barium, antimony.
6. A primer composition as in claim 5 comprising DDNP as the primary explosive.

7. A primer composition as in claim 6 comprising PETN as a secondary explosive.
8. A primer composition as in claim 7 comprising tetrazene to increase sensitivity to friction.
- 5 9. A primer composition as in claim 8 comprising KNO_3 predominating as the principal source of oxygen and $\text{ZnO} \cdot \text{ZnO}_2$ (containing at least 50-60% of ZnO_2) as a secondary oxidizer.
- 10 10. A primer composition as in claim 9 comprising silicon carbide (carborundum) as a frictionator.
11. A primer composition as in claim 10 comprising aluminum powder as the fuel.
12. A prime composition as in claim 11 comprising arcylic resin as a binder.

13. A primer composition comprising the following components by percentage weight:

	Component	% Weight
5	DDNP	20 - 30
	PETN	2 - 4
	Tetrazene	7 - 12
	KNO ₃	25 - 30
	Nitrocellulose	0.5 - 1.5
10	ZnO.ZnO ₂	15 - 20
	SiC	5 - 7
	Aluminum	5 - 10
	Acrylic resin	1.

14. A primer composition comprising the following components by percent weight preferred:

15	DDNP	30
	PETN	2
	Tetrazene	8
	KNO ₃	26
	Nitrocellulose	1
20	ZnO.ZnO ₂	17
	SiC	7
	Aluminum	8
	Acrylic resin	1.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 98/00182

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C06C7/00 C06B45/34

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C06C C06B C06D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 125 684 A (R.V. CARTWRIGHT) 30 June 1992 see column 3, line 62 - column 4, line 2; claims	1
X	US 5 417 160 A (G.C. MEI ET AL.) 23 May 1995 cited in the application see column 4, line 50 - line 59; claims	1
X	US 5 167 736 A (G.C. MEI ET AL.) 1 December 1992 cited in the application see column 4, line 1 - line 16; claims	1
A	EP 0 704 415 A (ELEY LIMITED) 3 April 1996 see page 5, line 35 - line 37; claims: example M	1
-/--		



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"S" document member of the same patent family

Date of the actual completion of the international search

18 November 1998

Date of mailing of the international search report

27/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+31-70) 340-3016

Authorized officer

Schut, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 98/00182

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.
A	GB 393 956 A (IMPERIAL CHEMICAL INDUSTRIES LIMITED ET AL.) 13 July 1933 see page 1, line 45 - line 81 ---	1
A	GB 806 278 A (E.I. DU PONT DE NEMOURS AND COMPANY) 23 December 1958 see page 1, line 77 - page 2, line 35; claims ---	1
A	DE 24 12 523 A (L'ETAT FRANCAIS REPRESENTÉ PAR LE DELEGUE MINISTERIEL POUR L'ARMEMENT) 26 September 1974 see page 15; claims ---	1
A	US 2 821 466 A (E.J. RUSSELL) 28 January 1958 see column 1, line 36 - line 40; claims ---	1
A	US 1 971 502 A (J. PICCARD) 28 August 1934 see column 1, line 47 - line 73; claims ---	1
A	US RE22285 E (S.B. LARGE ET AL.) 9 March 1943 see page 4, left-hand column, line 18 - line 35 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

In International Application No

PCT/CA 98/00182

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5125684 A	30-06-1992	NONE	
US 5417160 A	23-05-1995	AU 679301 B	26-06-1997
		AU 1178095 A	19-06-1995
		BR 9408216 A	26-08-1997
		CA 2177482 A	08-06-1995
		CN 1136802 A	27-11-1996
		CZ 9601593 A	11-09-1996
		EP 0737174 A	16-10-1996
		FI 962309 A	31-05-1996
		IL 111800 A	22-02-1998
		JP 9506326 T	24-06-1997
		NO 962262 A	31-07-1996
		WO 9515298 A	08-06-1995
		ZA 9409583 A	15-08-1995
US 5167736 A	01-12-1992	AT 162167 T	15-01-1998
		AU 662770 B	14-09-1995
		AU 2907592 A	07-06-1993
		BG 61604 B	30-01-1998
		BG 98746 A	31-05-1995
		BR 9206708 A	24-10-1995
		CA 2122710 A	13-05-1993
		CZ 9401100 A	15-12-1994
		DE 69224081 D	19-02-1998
		DE 69224081 T	13-08-1998
		DK 660812 T	09-02-1998
		EP 0660812 A	05-07-1995
		ES 2111084 T	01-03-1998
		FI 942051 A	04-05-1994
		HU 68124 A, B	29-05-1995
		JP 7500562 T	19-01-1995
		NO 941631 A	03-05-1994
		SK 51094 A	09-11-1994
		WO 9309073 A	13-05-1993
EP 704415 A	03-04-1996	AU 686851 B	12-02-1998
		AU 3024495 A	14-03-1996
		CA 2156974 A	28-02-1996
		US 5538569 A	23-07-1996

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 98/00182

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 393956 A		DE 574241 C	
GB 806278 A		NONE	
DE 2412523 A	26-09-1974	FR 2309493 A US 3956038 A	26-11-1976 11-05-1976
US 2821466 A	28-01-1958	NONE	
US 1971502 A	28-08-1934	NONE	
US RE22285 E		NONE	